

PRODUCT SPECIFICATION



VIBULK

Bulky, graphic paper; made mainly from mechanical fibres combined with bleached pulp.

PROPERTY		UNIT	VALUE				
Grammage	ISO 536	g/m ²	50	60	70	80	± 2%
Opacity	ISO 2471	%	86	90	92	95	min.
Specific volume	ISO 534	cm ³ /g	1.55-1.80	1.55-1.80	1.55-1.80	1.55-1.80	± 4%
Ash	ISO 2144	%	3.5	3.5	3.5	3.5	± 1.5
Moisture	ISO 287	%	7.0	7.0	7.0	7.0	± 0.5
Breaking strength	ISO 1924	N	35	35	35	35	min.
Brightness (R 457)	ISO 2470	%	78	78	78	78	± 2
Colour	ISO 5631-2						
L			92	92	92	92	± 1
a			-0.2	-0.2	-0.2	-0.2	± 0.5
b			6.0	6.0	6.0	6.0	± 0.5

OTHER CHARACTERISTICS

Reel dimensions:

- a) width (cm): 25 – 196 (combination of max. 13 reels)
- b) diameter (mm): max. 1250

Reel marks:

- a) inner side: unwinding direction mark
- b) joints - marked: max. 2 per reel
- c) outer side: producer's name, paper grade, order, reel No., basis weight (g/m²), reel width & diameter (cm), reel length (m), core diameter (cm), gross weight (kg), PM, PO, date

Sheet dimensions:

A1 (B1) – A0 deviations according to the ISO 216 Standard

Pallet marks:

producer's name, paper grade, order, pallet No., sheet size (mm), grain direction, basis weight (g/m²), number of sheets, PO, theor. & gross & net weight (kg)

APPLICATION

For publications and books in black&white and multi-colour cold-set and heat-set offset printing, as well as digital printing, also for sheet-fed printing; for cash register rolls.

PACKING

Reels wrapped in multiple layers of waterproof paper laminate.

NOTES

Ecological grade; ECF.

FSC®: FSC Mix Credit certified product can be provided upon request.

Quality Control Manager
Sandra Lileg

Technology & Development Manager
Danijel Oštir