

PRODUCT SPECIFICATION

VIPACK W

R

Wrapping/packaging paper; made mainly from bleached kraft sulphate pulp in combination with recycled fibres.

| PROPERTY | | UNIT | VALUE | | |
|-----------------------------|------------|---------------------|-----------------------|-----------------------|-------|
| Grammage | ISO 536 | g/m ² | 70 | 80 | ± 3% |
| Moisture | ISO 287 | % | 6.5 | 6.5 | ± 0.5 |
| Cobb H ₂ O (60s) | ISO 535 | g/m ² | 25 | 25 | ± 5 |
| Break. str. m.d./c.d. | ISO 1924 | N | 60 / 24 | 65 / 26 | Min. |
| Stretch m.d./c.d. | ISO 1924 | % | 1.50-2.00 / 3.87-5.73 | 1.50-2.00 / 3.87-5.73 | |
| Tear index m.d./c.d. | ISO 1974 | Nm ² /kg | 7.5 / 9.0 | 7.5 / 9.0 | ± 10% |
| Burst | ISO 2758 | kPa | 200 | 210 | ± 10% |
| Roughness Bendtsen | ISO 8791-2 | ml/min | 250 – 750 | 250 – 750 | ± 50 |
| Brightness (R 457) | ISO 2470 | % | 80 | 80 | ± 3 |
| Colour | ISO 5631-2 | | | | |
| L | | | 89.5 | 89.5 | ± 2.0 |
| a | | | 1.0 | 1.0 | ± 0.5 |
| b | | | -4.5 | -4.5 | ± 1.0 |

OTHER CHARACTERISTICS

Reel dimensions:

- a) width (cm): 30 – 196 (combination of max. 9 reels)
- b) diameter (mm): max. 1250

Reel marks:

- a) inner side: unwinding direction mark
- b) joints - marked: max. 2 per reel
- c) outer side: producer's name, paper grade, order, reel No., grammage (g/m²), reel width & diameter (cm), reel length (m), core diameter (cm), gross weight (kg), PM, PO, date

Sheet dimensions:

A1 (B1) – A0 deviations according to the ISO 216 Standard

Pallet marks:

producer's name, paper grade, order, pallet No., sheet size (mm), grain direction, grammage (g/m²), number of sheets, PO, theor. & gross & net weight (kg)

APPLICATION

For bags/sacks and various wrapping material; for flexo and offset printing.

PACKING

Reels wrapped in multiple layers of waterproof paper laminate.

NOTES

Ecological grade; ECF; made from ECF / TCF pulp and recycled fibres obtained from recovered paper in deinking process.

Technology & Development Manager
Danijel Oštir